

MAKO 8x

The 8-page CTP for high quality imaging and press format flexibility at the lowest cost of operation

Breaking the price barrier for 8-page CTP, the **MAKO 8x** makes 8-page CTP affordable for all commercial printers. It covers all formats for 2, 4, 6 and 8-page signatures with resolutions from 1800 dpi to 3556 dpi, with the lowest operating cost in the industry. With a maximum format of 32.4" x 45.0" (824mm x 1143mm) and production speeds up to 20 Speedmaster 102 plates per hour, the MAKO 8x keeps multipress environments efficient through flexible, fast and trouble-free performance.

- Utilizing the latest 120 mw violet laser technology our future-proof design allows a smooth transition to violet chemistry-free plate technology.
- The MAKO 8x employs an auto-pinch/auto-image feature for true hands-free operation after initial plate positioning.

- Supports press formats from 228mm x 252mm (8.9" x 9.9") to 824mm x 1143mm (32.4" x 45.0").
- Flexible – ECRM's patented press registration pin bars allow for both edge and notch registration, matching a wider range of press requirements.
- Open-ended software system accepts 1-bit TIFF files – choose the solutions you want. ECRM is here to help.
- No hidden extras – our online conveyor is standard on all MAKO CTP, allowing for a direct connection to the processor at no extra cost.
- Uses a straight-through plate path for easy operation and automated delivery to the processor.
- Bundled with CtServer Professional – ECRM's enhanced 1-bit TIFF server. Our open-ended software system accepts 1-bit TIFF files – choose the solutions you want. ECRM is here to help.
- Basic electricity requirements and quick installation – no dedicated power line needed. Lowest energy consumption in the industry – draws the same energy as a PC.
- Modular design keeps maintenance simple and costs low.
- Simple and intuitive operator interface makes training easy for everyone.



Choose ECRM for your Violet CTP solutions

ECRM products offer the lowest total cost of ownership in the business and the highest quality performance in the industry. Our manufacturing facility is located in Tewksbury, Massachusetts, USA and is certified as being in conformity to ISO 9001:2000 standards. Our signature flexible design lets you decide what's best for your CTP system, workflow, plates and processors. We support you every step of the way and work with you to ensure complete system integrity.



MAKO 8x CTP Specifications

Plate Sizes	Maximum: 824mm x 1143mm (32.4" x 45.0") Minimum: 228mm x 252mm (8.9" x 9.9")
Plate Thickness	0.14mm to 0.35mm (0.0055" to 0.014")
Media Types	Violet-sensitive photopolymer and silver halide metal plates. See media specifications for safe-light information.
Recording Source	120 mw violet laser diode (405 nm)
Resolutions	Five resolutions from 1800 to 3556 dpi Resolutions include: 1800, 2400, 2540, 3048, and 3556dpi
Maximum Line Screen	Up to 200 lpi (78.7 lpcm). Media dependent
Repeatability	0.025mm (0.001") typical May vary according to media type and processing conditions
Processing	Online: The plate transport automatically moves the plate into the processor.
Environmental	Power: 100 - 240 Volts; 3 Amps; 250 watts maximum; 50/60Hz, single phase Heat Dissipation: 850 BTU/hour
Interface	USB 2.0 High Speed. 3 meter host cable provided.
Operating Conditions	62 - 86° F (17 - 30° C); relative humidity 45 - 65%, noncondensing. Relative humidity outside of this range may affect performance. Operating conditions outside plate media specifications may affect performance.
Weight	409 kg (900 lbs.)
Footprint Dimensions	Width: 106.7cm (42.0") Length: 244.8cm (96.4") Height: 189.2cm (74.5")

ECRM[®]
imaging systems

Headquarters:

554 Clark Road
Tewksbury, MA 01876
USA
Tel: (+1) 978.851.0207
Fax: (+1) 978.851.7016
sales@ecrm.com
www.ecrm.com

International Sales Offices:

3 Century Court, Tolpits Lane Watford, Hertfordshire WD18 9PU, UK Tel: (+44) 1923.218.255 Fax: (+44) 1923.218.256 sales_uk@ecrm.com	B2, 10/F, Block B, Kailey Industrial Centre, 12 Fung Yip Street, Chai Wan, Hong Kong Tel: (+852) 2564-8989 Fax: (+852) 2564-8821 sales_hk@ecrm.com sales_asia@ecrm.com
--	---

All ECRM products carry the CE mark. All products are NRTL Certified. Class 1 Laser Products ECRM's Tewksbury facility is ISO 9001:2000 certified.

All trademarks are the property of their respective owners and their use in this documentation is acknowledged and recognized. The information provided in this document is subject to change without notice.